


Versatile system for most residential design needs



# **EC**45

EC45 is Thermeco's most popular and adaptive system to suit Australia's broad and dynamic environmental conditions.



### Single or Double Glazing

Excellent thermal & acoustic insulation available in a range of up to 30mm thickness to suit installation requirement.

#### Frame —

Gasket

Made from EPDM provides initial protection for wind & water penetration.

#### **Opening Styles** Awning Turn & Tilt **Hinged Doors** Fixed Tilt In Casement Style Standard Savio OS Standard Savio OS 1200 1200 1700 1700 1200 1500 Max Width 1000 Various 2000 **Max Height** 2500 2700 2000 2500 2200 3000 Max Weight (kg) 40 100 80 100 80 100 80





Architect: Gardiner Architects | Builder: Constructing Spaces



Design & Build: Englehart Homes

### **Features & Benefits**



Low maintenance

Maximum wind and water tightness

Increased airflow & greater ventilation control



Multi-position locking for added strength & security



Long lasting & corrosion resistant



Beauty & design



### **Energy Rating WERS**

		Casement		Fixed	
Glazing	υ	SHGC	υ	SHGC	
6mm Clear Toughened / 12mm Argon / 6mm Clear Toughened	4.3	0.44	3.2	0.60	
6mm Energy Tech / 12mm Argon / 6mm Clear Toughened	3.9	0.38	2.5	0.52	
6mm Performa Tech / 12mm Argon / 6mm Clear Toughened Grey	3.7	0.21	2.3	0.27	
6mm Insulmax 564 / 12mm Argon / 6mm Clear Toughened	3.7	0.19	2.3	0.24	
6mm Sunergy Clear / 12mm Argon / 6mm Clear Toughened	4.0	0.32	2.7	0.43	
6.38mm Clear ComfortPlus / 12mm Argon / 6mm Clear Toughened	3.9	0.38	2.5	0.51	
6mm LightBridge / 12mm Argon / 6mm Clear Toughened	3.8	0.36	2.4	0.48	



Design & Build: Salerno Homes

## Windows for meaningful living.





**Authorised Fabricator** 



15 Kelletts Road, Rowville 3178, Victoria, Australia Phone: 03 9763 1089 Fax: 03 9923 6263 windows@thermeco.com.au



\*The images displayed on this brochure may not always exactly relate to the specified series and are used as representation only.